Technical Documentation of (EU) No 617/2013

Product type	Integrated des	ktop computer
Product category	С	D
NA an ufacturar a casa and dua ca	Acer Italy s.r.l,	
Manufacturer name, address	Via Lepetit, 40, 20020) Lainate (MI) Italy
Product model number	Aspire AZ3-115	
Year of manufacture	20	14
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	188 kWh/year	211 kWh/year
are disabled (from 1 July 2014)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	222 kWh/year	249 kWh/year
are enabled (from 1 July 2014)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	134 kWh/year	150 kWh/year
are disabled (from 1 January 2016)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	152 kWh/year	172 kWh/year
are enabled (from 1 January 2016)		
Whether all discrete graphics card are	Yes	Yes
enabled during the test	165	165
Whether switchable graphics mode with	No	No
UMA is driving the display during the test	110	INO
E _{TEC} of highest power-demanding	68.77 kWh/year	67.02 kWh/year
configuration	00.77 KVVII/year	07.02 KVVII/yeai
Idle state power demand	18.71 Watt	18.25 Watt
Sleep mode power demand	2.95 Watt	2.95 Watt
Sleep mode with WOL enabled power	3.01 Watt	3.01 Watt
demand		
Off mode power demand	0.398 Watt	0.37 Watt
Off mode with WOL enabled power	0.41 Watt	0.381 Watt
demand		
Maximum power demand	Not applicable	Not applicable
Internal power supply (IPS) efficiency at		
10 %, 20 %, 50 % and 100 % of rated	Not applicable	Not applicable
output power		
External power supply's (EPS) average	87.94%	87.94%
active efficiency	01.94%	01.94%
Noise levels (the declared A-weighted	3.0 B	3.0 B
sound power level, L _{WAd}) of idle mode	3.U B	3.U D

Noise levels (the declared A-weighted		
sound power level, L _{WAd}) of "HDD random	3.4 B	3.4 B
seek" mode		
Minimum number of loading cycles that	Not applicable	Not applicable
the batteries can withstand		
Configuration of memory	2GB	4~8GB
Configuration of internal storage	1 piece	1 piece
Configuration of discrete television tuner	0 piece	0 piece
Configuration of discrete audio card	0 piece	0 piece
Configuration of discrete graphics cards	1 piece	1 piece
Configuration of discrete graphics cards	G1	G1
category	GT	GT
The battery in this product cannot be	Not applicable	Not applicable
easily replaced by users themselves	Not applicable	Not applicable
For products with an integrated display,	0 mg	0 mg
the total content of mercury is	0 mg	O mg
Measurement methodology for E _{TEC}	COMMISSION REGUES 617/2013 of 26 June Directive 2009/125/EP Parliament and of the to ecodesign requirer and computer servers ANNEX II Ecodesign timetable: 1.1.1. E _{TEC} formula.	2013 implementing C of the European Council with regard ments for computers S:
Measurement methodology for idle mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.4. Measuring long idle mode; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy; Annex E.2 (informative) ENERGY STAR® V5 compliant testing methodology.	

Measurement methodology for sleep mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.
Measurement methodology for off mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.
Measurement methodology for IPS efficiency	Not applicable
Measurement methodology for EPS efficiency	EN 50563:2011 External a.c.—d.c. and a.c.—a.c. power supplies — Determination of no-load power and average efficiency of active modes.

Measurement methodology for noise level	ECMA-109 2 nd edition (December 1987) Declared Noise Emission Values of Computer and Business Equipment: 4. Determination of the declared noise emission values. ECMA-74 11 th edition (December 2010) Measurement of Airborne Noise emitted by Information Technology and Telecommunications Equipment: 5. Installation and operating instructions; 6. Method for determination of sound power levels of equipment in reverberation test rooms; 7. Method for determination of sound power levels of equipment under essentially free-field conditions over a reflecting plane; Annex C.15 Equipment category: personal computers and workstations.
Measurement methodology for battery loading cycles	Not applicable
Sequence of steps for achieving a stable condition with respect to power demand	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.3.3. Measuring sleep mode; 5.3.4. Measuring long idle mode.
Description of how sleep mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode.
Description of how off mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode.

Sequence of events required to reach the mode where the equipment automatically changes to sleep mode Sequence of events required to reach the mode where the equipment automatically	ENERGY STAR® Program Requirements Product Specification for Computers, Eligibility Criteria Version 6.0, Rev. Oct- 2013: 1.D.4 Sleep Mode. Not applicable
The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode	30 minutes
The length of time before the display sleep mode is set to activate after user inactivity	10 minutes
User information on the energy-saving potential of power management functionality	http://www.energystar.gov/index.cfm?c=po wer_mgt.pr_power_mgt_users
User information on how to enable the power management functionality	http://www.energystar.gov/index.cfm?c=po wer mgt.pr power mgt users
Test parameter for ambient temperature Test parameter for test voltage Test parameter for frequency Test parameter for total harmonic distortion of the electricity supply system	25 °C 230 V 50 Hz 3 %
Test parameter for information and documentation on the instrumentation, set-up and circuits used for electrical testing	Digital Power Meter- Yokogawa WT210 Programmable AC Soure- Chroma 61603