Technical Documentation of (EU) No 617/2013

Product type	Integrated des	ktop computer
Product category	С	D
	Acer Italy s.r.l,	
Manufacturer name, address	Via Lepetit, 40, 20020	D Lainate (MI) Italy
Product model number	Aspire	Z1-611
Year of manufacture	20	14
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	188 kWh/year	215 kWh/year
are disabled (from 1 July 2014)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	Not Applicable	Not Applicable
are enabled (from 1 July 2014)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	134 kWh/year	154 kWh/year
are disabled (from 1 January 2016)		
E _{TEC} allowance with capability		
adjustments when discrete graphics cards	Not Applicable	Not Applicable
are enabled (from 1 January 2016)		
Whether all discrete graphics card are	Not applicable	Not applicable
enabled during the test	Not applicable	Not applicable
Whether switchable graphics mode with	Not applicable	Not applicable
UMA is driving the display during the test		Not applicable
E _{TEC} of highest power-demanding	58.823 kWh/year	70.293 kWh/year
configuration	50.025 KWII/year	TU.295 KVIII/year
Idle state power demand	15.84 Watt	19.98 Watt
Sleep mode power demand	1.402 Watt	1.284 Watt
Sleep mode with WOL enabled power	1.402 Watt	1.279 Watt
demand		
Off mode power demand	0.155 Watt	0.293 Watt
Off mode with WOL enabled power	0.4833 Watt	0.857 Watt
demand		
Maximum power demand	Not applicable	Not applicable
Internal power supply (IPS) efficiency at		
10 %, 20 %, 50 % and 100 % of rated	Not applicable	Not applicable
output power		
External power supply's (EPS) average	07 700/	07.000/
active efficiency	87.73%	87.80%
Noise levels (the declared A-weighted	040	
sound power level, L_{WAd}) of idle mode	3.1 B	3.1 B

Noise levels (the declared A-weighted		[
, , , , , , , , , , , , , , , , , , ,	0.4 5	0.4 D
sound power level, L _{WAd}) of "HDD random	3.1 E	3.1 B
seek" mode		
Minimum number of loading cycles that	Not applicable	Not applicable
the batteries can withstand	2G	2G-8G
Configuration of memory Configuration of internal storage		
Configuration of discrete television tuner	1 piece 0 piece	1 piece 0 piece
Configuration of discrete audio card	0 piece	0 piece
Configuration of discrete graphics cards	0 piece	0 piece
Configuration of discrete graphics cards		
category	Not applicable	Not applicable
The external package of the notebook		
provides the information, "The battery in	Nataralian	Net englischie
this product cannot be easily replaced by	Not applicable	Not applicable
users themselves."		
For products with an integrated display,		
the total content of mercury is	0 mg	0 mg
Measurement methodology for E _{TEC}	COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers: ANNEX II Ecodesign requirements and timetable: $1.1.1. E_{TEC}$ formula.	
Measurement methodology for idle mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.4. Measuring long idle mode; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy; Annex E.2 (informative) ENERGY STAR [®] V5 compliant testing methodology.	

Measurement methodology for sleep mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.
Measurement methodology for off mode	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.4. Test conditions; 5.7. True RMS watt meter specification; 5.8. True RMS watt meter accuracy.
Measurement methodology for IPS efficiency	Not applicable
Measurement methodology for EPS efficiency	EN 50563:2011 External a.c.—d.c. and a.c.—a.c. power supplies — Determination of no-load power and average efficiency of active modes.

Measurement methodology for noise level	ECMA-109 2 nd edition (December 1987) Declared Noise Emission Values of Computer and Business Equipment: 4. Determination of the declared noise emission values. ECMA-74 11 th edition (December 2010) Measurement of Airborne Noise emitted by Information Technology and Telecommunications Equipment: 5. Installation and operating instructions; 6. Method for determination of sound power levels of equipment in reverberation
	test rooms; 7. Method for determination of sound power levels of equipment under essentially free-field conditions over a reflecting plane; Annex C.15 Equipment category: personal computers and workstations.
Measurement methodology for battery loading cycles	Not applicable
Sequence of steps for achieving a stable condition with respect to power demand	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode; 5.3.3. Measuring sleep mode; 5.3.4. Measuring long idle mode.
Description of how sleep mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.3. Measuring sleep mode.
Description of how off mode was selected or programmed	EN 62623:2013 — Desktop and notebook computers — Measurement of energy consumption: 5.2. Test setup; 5.3.2. Measuring off mode.

Sequence of events required to reach the mode where the equipment automatically changes to sleep mode	ENERGY STAR [®] Program Requirements Product Specification for Computers, Eligibility Criteria Version 6.0, Rev. Oct- 2013: 1.D.4 Sleep Mode.
Sequence of events required to reach the mode where the equipment automatically changes to off mode	Not applicable
The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode	30 minutes
The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode	30 minutes
The length of time before the display sleep mode is set to activate after user inactivity	10 minutes
User information on the energy-saving potential of power management functionality	http://www.energystar.gov/index.cfm?c=po wer_mgt.pr_power_mgt_users
User information on how to enable the power management functionality	http://www.energystar.gov/index.cfm?c=po wer_mgt.pr_power_mgt_users
Test parameter for ambient temperature	25 ℃
Test parameter for test voltage	230 V
Test parameter for frequency	50 Hz
Test parameter for total harmonic	3 %
distortion of the electricity supply system	
Test parameter for information and documentation on the instrumentation,	Digital Power Meter- Yokogawa WT210
set-up and circuits used for electrical testing	Programmable AC Soure- Chroma 61603