

fax it, say it

The magic3⁻² voice dect comes with a DECT cordless handset and a high quality answering machine. Moreover, handsfree speaking and distinctive ringtones make communicating even more enjoyable. Be it at home or in the office - the stylish design of the magic3⁻² voice dect fits into each environment.



DECT cordless handset

- GAP compatible handset
- 20 number phone book on handset

Ink-film fax

- 14400bps modem speed
- 50 page memory

Telephone

- 200 name dial entries
- Handsfree speaking

Answering machine

- Recording time up to 30 minutes
- VIP code

Copier

- Multicopy up to 15 pages
- Zoom-function (enlarge/reduce)



Main features

DECT cordless handset

- GAP compatible (up to 6)
- Up to 300 m range
- 120 hours stand by time, 10 hours talk time
- 20 number phone book on handset
- 6 handset ringer melodies
- 3 x AAA NiMH

Ink-film fax

- ITU Group 3 compatible (T.30 standard/T.30 new)
- 14400bps modem speed, auto fall back
- Horizontal resolution: 8 pixels/mm, vertical resolution standard: 3.85 lines/mm, vertical resolution fine: 7.7 lines/mm
- Page header
- Automatic redial
- Sending report with reduced copy of the first page
- Printing method: thermal transfer
- 10 page automatic document feeder (ADF)
- Timer function
- 50 page memory
- Group broadcasting
- Easy polling (receive and send)
- Paper tray up to 50 pages
- Cordless phone management

Telephone

- 200 name dial entries
- 10 ringer melodies
- Distinctive ringtones*
- 10 short dial keys
- On hook dialling
- Chain dialling
- Handsfree speaking
- Redial of the last 10 numbers
- Outgoing call log print
- Caller identification**

Answering machine

- Recording time up to 30 minutes
- Direct message access (first 10 messages)
- Current call recording
- Pre-recorded OGM
- Message forwarding
- VIP-Code

Copier

- Multicopy up to 15 pages
- Fine-/photo-resolution
- Zoom-function (enlarge/reduce)
- 64 grey scales

* Depends on availability of caller identification

** Depends on the availability of the service on the local operators network

General information

12 NC	9061 173 30XXX
Type number	PPF 581R/XXS
EAN code	3 425160 156XXX
Designed for	PSTN/PABX
Power supply	195-264 V AC/47-63 Hz

Power consumption

• Stand by	< 2 W
• Transmission	15 W
• Reception	15 W
• Copy	15 W
• Telephone conversation	4 W

Display

- Liquid crystal-display (LCD), 16 characters/
1 line, european characters

Installation

- Easy-install menu and help pages

Dimension (WxDxH)

• Unpacked	318 x 210 x 150 mm
• Packed	410 x 290 x 230 mm

Weight

• Unpacked	2,6 kg
• Packed	3,6 kg

Temperature range

• Operation	5° C - 40° C
• Storage packed	-25° C - 50° C
• Storage unpacked	0° C - 45° C

Relative humidity

• Operation	15 - 85 %
• Storage packed	5 - 95 %
• Storage unpacked	15 - 85 %

Standard package includes

- Fax machine incl. cables (main and telephone network)
- DECT handset
- Starter ink film
- User-manual including installation-guide

Accessories

- Philips PFA 331 with PLUG'N'PRINT Card/up to 140 pages A4



www.fax.philips.com

© 2005 SAGEM Communication Austria GmbH.
All rights reserved. The information and specifications included are subject to change without prior notice. SAGEM tries to ensure that all information in this document is correct, but does not accept liability for error or omission.