



# TOTAL DIGITAL IMAGING SYSTEM

*At the heart of the image*





# We've Got You Covered

## Make Your Photography Matter with the Nikon Total Digital Imaging System

So you have a digital SLR and an idea — a GREAT idea — for a photograph. Do you have all you need to make that idea happen? A quick look through these pages and you'll know. Here you'll find all the accessories available for the Nikon

D-SLR lineup: everything you need to realize your present ideas, and inspire new ones. Whether you are a seasoned professional or a passionate weekend shooter, we're sure you'll find something in this brochure that can help you craft better images. Every item found within is designed specifically for Nikon cameras, giving you seamless performance that truly brings out the best in you and your Nikon D-SLR. Got an idea?

Make it happen. Here's where you start.



# C O N T E N T S

## See what one Nikon Speedlight can do

*Easy, intelligent, amazing:  
The Nikon Creative Lighting System*



pp4-5




## Dramatic close-up lighting made easy

*Explore fine details with flexible, wireless control*



pp8-9



## Make lighting work for you with wireless multiple Speedlights

*Turn good shots into great shots with Advanced Wireless Lighting*




pp6-7



## Your file, your vision

*Capture NX Software:  
master post-production*



pp13-15



## Which Speedlight is right for you?

*Nikon Creative Lighting System compatible Speedlights*

pp10-11

## Flash Accessories


p12

## Power when you need it

*Battery packs and power management*




p16



## View with clarity and comfort

*Viewing attachments*



p18




## Communication technology for any location

*GPS cable/wireless transmitters*



p16



## Close in on every subject

*Close-up accessories*



p19




## Steady shots — night or day

*Remote control accessories*



p17



## System diagram

pp20-21

## Nikkor lens lineup

p22

## Nikon digital SLRs

p23

# See what one Nikon Speedlight can do




© Gordon Nash

## Gordon Nash — Wedding photographer (U.S.A.)

I shoot about 50 weddings a month, and nearly half of my images need a Nikon Speedlight. I always have one on my camera, with another ready for side-lighting or other handheld effects. Each Speedlight makes a dramatic difference to the finished image. For the above image, I used one SB-800 for side-lighting and a soft-focus filter on the lens for a dreamy look.

As a professional wedding photographer, I face moving subjects, unpredictable shooting situations and limited prep time, so speed and intuition are vital to my success. That's why I depend on the Nikon



Creative Lighting System. It's easy to use and offers so many options, along with consistent exposure and performance. I have to be ready for that special moment at all times. The Creative Lighting System helps me do that.

<http://www.gordonnash.com>



**Camera setting data:**  
Camera and  
Speedlights: D200  
(built-in Speedlight as  
commander) and SB-

800 (remote unit)  
Lens: AF 85mm f/1.8D  
Shutter speed: 1/125 sec.  
Aperture: f/2.2  
Exposure mode: Aperture-Priority Auto  
Flash mode: i-TTL  
Image quality: RAW

## Easy, intelligent, amazing: The Nikon Creative Lighting System

Lighting is a vital component of all images, but the past complexities of flash photography have made many photographers — even seasoned ones — hesitant to explore its full potential. Not any more. Working photographers around the world are discovering how Nikon's Creative Lighting System brings simplicity and real-world usability to flash photography. The key is Nikon's breakthrough i-TTL flash control technology. With this at its core, Nikon Speedlights offer consistently accurate flash exposures that can adjust to nearly any lighting situations you face. Nikon Speedlights communicate with your Nikon D-SLR to perform all the complex lighting calculations for you. Nikon's exclusive monitor pre-flash offers precise feedback information, registering everything from available light and shadows to color temperature and reflective surfaces within the scene. The camera also integrates information from its built-in database of over 30,000 actual scenes to determine the ideal exposure — all within a millisecond before each shutter release. Whether on top of the camera or used as a wireless remote unit, Nikon's Creative Lighting System offers the most dependable and consistent flash exposure in the business.



## Bright lights, big ideas – with only one Nikon Speedlight, you can:




SB-800 attached

© Joe McNally

### Go the distance: more flash power

The Speedlights built into Nikon D-SLRs are smart and responsive, but sometimes your subject is far enough away that you simply need more flash power. Connect a Nikon external Speedlight and you can capture subjects at a much greater distance with more balanced illumination.



Built-in Speedlight



Bounce flash

© Gordon Nash

### Soften the light: bounce flash

Direct light can be harsh and leave a distracting shadow behind your subject. Try turning the flash head toward a wall or ceiling and you'll soften the light and get rid of the shadow, creating a more flattering atmosphere for portraits.



Direct flash



Auto FP High-Speed Sync stops the action  
Shutter speed: 1/3200 sec.


© Joe McNally

### Capture the action: Auto FP High-Speed Sync

Indispensable to outdoor photography, this enables action-stopping shutter speeds with fill flash. It is also important to portraiture, allowing you to use larger apertures for a more pleasingly radiant ambient light. Your camera will automatically set itself to this mode if the shutter speed rises above the camera's standard flash sync speed of 1/250 second.



Normal sync




Main subject's exposure stays the same  
regardless of any compositional changes.

© Joe McNally

### Maintain the exposure: Flash Value (FV) Lock

The FV Lock (Flash Value Lock) maintains the same flash value for correct exposure during a sequence of photographs, allowing you to zoom in on your subject, change the composition or adjust the aperture, all without altering your intended exposure. That way you can concentrate on capturing your subject without worrying about adjusting the lighting.



Original exposure

### Nikon's exclusive i-TTL: a higher level of accuracy

The real breakthrough is Nikon's monitor pre-flash. It is designed to provide your Nikon D-SLR with consistently accurate feedback information in order to achieve ideal flash output. This level of accuracy is found nowhere else.



i-TTL Balanced Fill-Flash

### Speedlight tips: Diffuser

Use a diffuser above the flash to soften the light and eliminate harsh shadows. This is useful in almost any flash situation, including fill flash, for natural looking skin.




# Make lighting work for you with wireless

## Joe McNally — Photojournalist (U.S.A.)


There have been many difficult lighting situations in my career where the Nikon Creative Lighting System literally amazed me by sorting out a proper exposure. The System offers incredibly high accuracy in most shooting scenarios. Milliseconds before each shot, the camera meter and Speedlight speak to each other, relaying and calculating massive amounts of lighting information — exposure variance, RGB, reflectance, distance and contrast, to name a few — all of which are constantly shifting and changing. I've always said that no camera system will ever solve every problem, but Nikon cameras and the Creative Lighting System do a phenomenal job of sorting through the data to give you accurate exposures. This is a major reason to use Nikon.

<http://www.joemcnally.com>



**Camera setting data:**  
Camera and Speedlight:  
D2x and three SB-800s  
(one on-camera master/commander and two

remote units)  
Lens: AF-S DX 12-24mm f/4G IF-ED  
Shutter speed: 1/160 sec.  
Aperture: f/14  
Exposure mode: Aperture-Priority Auto  
Flash mode: i-TTL  
Image quality: RAW



## Turn good shots into great shots with Advanced Wireless Lighting

You can accomplish a lot with just one Speedlight, but sometimes an image would benefit from more artistic illumination. Adding more Speedlights not only adds depth to the scene but also character and charm to your subject. One of the greatest benefits that is singular to Nikon's Advanced Wireless Lighting is that controlling dozens of Speedlights is just as easy as controlling your on-camera Speedlight. And because it's wireless, setting up your Speedlights can be done quickly and smoothly no matter where you're shooting. From the Master Speedlight located on top of your camera, you can control the flash output of three groups of wireless remote units, adding any number of Speedlights to each of these groups.




Add Group B to emphasize the middle ground and Group C for the background


Simply set everything to Nikon's exclusive i-TTL for consistently accurate exposures in even the most difficult lighting situations. It's just as easy to explore alternate exposures by adjusting the flash exposure compensation of individual Speedlight groups. Or if you like, turn off a Speedlight group, or set everything to manual — all via the LCD panel on the Master Speedlight, all possible without ever leaving your camera. Multiple Speedlight control has never been this intuitive and fluid. No other lighting system comes close.



Group A illuminates the main subject from the side



You can control up to 4 groups of Speedlights, including the Master and 3 remote i-TTL Speedlight groups, to achieve complete control of your lighting environment. All groups can be controlled from the Master, and there is no limit to how many you can use.



Control it all from here. Set the flash mode, turn Speedlight groups on or off and control the flash exposure compensation for up to 4 Speedlight groups from the Master Controller SB-800's LCD panel.



# multiple Speedlights



© Joe McNally All images aside from product shots by Joe McNally


## Speedlight tips: colored gels

Selecting the right colored gel filter is important, especially when you want the flash to appear natural alongside ambient light. For the outrigger canoe photograph (shown left), an amber gel filter added extra warmth to the main subject while blending seamlessly with the sunlight and overall color of the image.




*SB-600 Speedlights can serve as remote units in wireless lighting, while SB-800 Speedlights can serve as Master, Commander or separate remote units.*

**Timing is crucial for location shooters. Here's how one photographer captured an aspiring dancer in 24 hours, and how the Nikon Creative Lighting System provided the speed and flexibility he needed.**




### Bounce flash

The illuminated space needed to be large enough for the dancer to move freely. Four SB-800 units were attached to the ballet bar to bounce light off the wall. Two more SB-800 units bounced light off the floor. By bouncing light off the cream-colored wall and the wooden floor, the lighting achieved natural warmth.






### Seamless flash with mixed ambient lighting

This shop had mixed light sources: fluorescent light along with sunlight from the window. To give the scene a natural look, a diffuser is attached to an SB-800 and tilted toward the ceiling, with an additional wireless remote SB-800 illuminating the dancer from outside the window.



### Directional light for a dramatic exposure

Shooting at sunset can offer beautiful ambient light, but in a narrow window of time. For a dramatic effect, two sets of SB-800 remote units illuminate the dancer from the front and the rear. After a few angle adjustments, there was a large enough volume of light to emphasize the dancer's shape appropriately.



# Dramatic close-up lighting made easy



© Foto Natura team

## Explore fine details with flexible, wireless control

Detail can be crucial to the impact of an image. That's why Nikon offers the ultimate tools for creative and versatile close-up lighting. Designed to work seamlessly with Nikon's i-TTL Wireless Creative Lighting System, both the R1C1 and R1 bring an amazing level of simplicity and automation to the lighting process.

Close-up lighting has countless uses for nearly every kind of subject matter. Hobbyists enjoy capturing ornamental patterns found on coins, flowers and other small objects, while people photographers take advantage of the shallow depth-of-field for intimate portraits. And with no wires to get in the way, you can handhold the Speedlights to make quick adjustments or to follow moving subjects, such as insects. From medical applications to food photography, the R1C1 and R1 will make you see things differently. Both the R1C1 and R1 contain a comprehensive assortment of accessories, including the SW-11 Extreme Close-up Positioning Adapter, the SJ-R200 Color Filter Set, the SW-12 Set Diffuser, the SW-C1 Flexible Arm Clip and a set of five adapter rings to ensure the SX-1 Attachment Ring can be mounted on virtually any Nikkor lens designed for close-range photography. Whichever set is right for you, both make mastering close-up flash photography simple, fascinating and fun.

### SU-800 Wireless Speedlight Commander

Simple operation lets you easily command wireless remote Speedlight operation.

### SX-1 Attachment Ring

Allows easy attachment and detachment of SB-R200 Speedlights to the lens.

### SB-R200 Wireless Remote Speedlight

Flexible, dependable flash control. Can be handheld, clamped on a stand or attached to the lens using the SX-1. The lighting angle can be adjusted by tilting the flash head.

### R1C1

R1C1 comes equipped with the SU-800, two SB-R200 Speedlights, and more.

### Nikon Wireless Close-up Speedlight System

### R1

R1 comes equipped with two SB-R200 Speedlights, and more.





## Wil Meinderts, Jan Vermeer and Danny Ellinger — Nature photographers at Foto Natura team (The Netherlands)

Nikon's Wireless Close-up Speedlight System is flexible, consistent and amazingly easy to operate. You can expect superb performance straight out of the box, with their small diffusers providing beautifully soft light. Whether attached to the camera or handheld, the two SB-R200 units included are capable of a wide range of lighting situations, but add an SB-800 or additional SB-R200 units, and you seamlessly control nearly every aspect of lighting – even in poorly lit locations. The 105 mm VR Macro lens is ideal for this type of shooting, especially when insects are your subjects, but for any serious macro photographer, the R1C1 is a must-have tool.

<http://www.fotonatura.com>



**Camera setting data:**  
Camera and Speedlight:  
D200 and R1C1  
Lens: AF-S VR Micro  
105mm f/2.8G IF-ED

Shutter speed: 1/125 sec.  
Aperture: f/13  
Exposure mode: Aperture-Priority Auto  
Flash mode: i-TTL  
Image quality: RAW

### Speedlight tips: close-up lighting

The SX-1 and SB-R200 Speedlights offer exciting creative possibilities for multiple lighting.



The SU-800 can also be bought separately, and features simpler operation and a wider range of options than the SB-800. And because there's no distracting pre-flash with the SU-800, some photographers prefer it when shooting people and animals.



© Foto Natura team

### Brighten your subject for natural beauty

Some subjects don't pose willingly. Here a butterfly momentarily lands on a vivid orange flower. The day was overcast, so three SB-R200 Speedlights were used: one is attached to the camera and pointed directly at the butterfly. Two off-camera units have been angled for side-lighting and background fill, with diffusers softening the light for a more natural look.




Location: Turtle Bay Resort

© Joe McNally

### Close-up lighting: Step-by-step


Sometimes small units make a big impact. The model holds a shard of mirror in front of her face, which is illuminated by two handheld SB-R200 remote units: one from above and one from below. After a little trial and error, the ideal angle and Speedlight positioning was determined. The result: a shot full of mystery and drama.



© Noriyuki Yuasa

### Reveal depth and space from ordinary objects

To create a sense of fantasy from simple ornamental glass, one SB-R200 was placed underneath, emphasizing the thinly carved rabbit relief. To draw out the blue, a second SB-R200 was placed behind the glass and angled downwards, with the extreme close-up positioning adapter SW-11 and diffuser SW-12 helping to create the illusion of a dual-tone blue background. The result: a dreamlike image of a rabbit running across the field at night.



# Which Speedlight is right for you?

**Ultimate flash performance: Nikon Creative Lighting System compatible Speedlights**



**SB-800**

**Powerful, Intelligent, Complete**  
Serves as Master, Commander or Remote Unit in Advanced Wireless Lighting

[for D2 series, D200, D80, D40 series]



**SB-600**

**Practical, Intelligent, Indispensable**  
Serves as Remote Unit in Advanced Wireless Lighting

[for D2 series, D200, D80, D40 series]



**SB-400**

**Compact, Intelligent, Versatile**  
i-TTL and Bounce Flash Capability

[for D2 series, D200, D80, D40 series]

## SB-800 Accessories (supplied)




### Bounce Adapter SW-10H

Softens the shadows and diffuse light during bounce flash by attaching the SW-10H over the flash head.



### Quick Recycling Battery Pack SD-800

Shorten recycling time to as little as 2.9 seconds in Manual mode at full output by attaching an additional battery.



### Colored Gel Filter Set SJ-800


Use these gels for correct color temperature in ambient lighting situations.



### Speedlight Stand AS-19

(comes with SB-800 / SB-600)

The AS-19 allows stable placement when used as a remote unit. A tripod socket is also provided.



### Colored Gel Filter Set SJ-1 (optional for SB-800/SB-600)

This set includes 8 types of colored gels for creative Speedlight options.

- FL-G1/G2 (for fluorescent light)
- TN-A1/A2 (for incandescent/tungsten light)
- BLUE
- YELLOW
- RED
- AMBER

## Creative Lighting System Features

- i-TTL Flash
- Advanced Wireless Lighting\*
- Modeling Flash\*
- FV (Flash Value) Lock (D2 series/D200/D80)
- Auto FP High-Speed Sync\* (D2 series/D200/D80)
- Wide-Area AF Assist Illuminator\*
- Flash Color Information Communication
- Distance Priority Manual Flash (SB-800)

\* Not available with the SB-400.

## Specifications

	SB-800	SB-600	SB-400
<b>Electronic construction</b>	Automatic Insulated Gate Bipolar Transistor (IGBT) and series circuitry		
<b>Guide number</b>	38 (ISO 100, m), 53 (ISO 200, m) (with zoom head set at 35mm)	30 (ISO 100, m), 42 (ISO 200, m) (with zoom head set at 35mm)	21 (ISO 100, m), 30 (ISO 200, m)
<b>Angle of coverage</b>	Auto power zoom 24mm, 28mm, 35mm, 50mm, 70mm, 85mm, 105mm; 17mm, 14mm with built-in wide-flash adapter; 14mm with soft dome	Auto power zoom 24mm, 28mm, 35mm, 50mm, 70mm, 85mm; 14mm with built-in wide-flash adapter	18mm
<b>Flash mode</b>	i-TTL; D-TTL; Auto Aperture; Non-TTL Auto; Manual (Full ~ 1/128 output); Distance-Priority Manual; Repeating Flash; Red-Eye Reduction	i-TTL; D-TTL; Manual (Full ~ 1/64 output); Red-Eye Reduction	i-TTL; Manual (with D40 series only)
<b>Flash exposure compensation</b>	-3.0 to +3.0 EV in increments of 1/6 steps in i-TTL or Auto Aperture flash modes	-3.0 to +3.0 EV in increments of 1/6 steps in i-TTL	—
<b>Minimum recycling time</b>	Approx. 2.5 seconds with the SD-800 (Manual at full)	Approx. 2.5 seconds with Nickel/Ni-MH batteries (Manual at full)	Approx. 2.5 seconds with Ni-MH batteries (Manual at full)
<b>Number of flashes</b>	Approx. 130 (Manual at full) (with alkaline batteries)	Approx. 200 (Manual at full) (with alkaline batteries)	Approx. 140 (Manual at full) (with alkaline batteries)
<b>Bounce capability</b>	Flash head tilts down to -7°, or up to 90°; flash head rotates horizontally 180° to the left or 90° to the right	Flash head tilts up to 90°; flash head rotates horizontally 180° to the left or 90° to the right	Flash head tilts up to 90° with click-stops at 0°, 60°, 75°, 90°
<b>AF-Assist Illuminator</b>	Automatically turns on when performing autofocus in dim light or in the dark		
<b>Power source</b>	Four AA-size alkaline/NiCd/Nickel/Ni-MH/lithium batteries; SD-8A, SK-6A/6	Four AA-size alkaline/NiCd/Nickel/Ni-MH/lithium batteries	Four AA-size alkaline/lithium/oxyride/Ni-MH batteries
<b>Mounting foot lock lever</b>	Provided	Provided	Provided
<b>Dimensions (W x H x D)</b>	Approx. 70.5 x 129.5 x 93.0mm	Approx. 68.0 x 123.5 x 90.0mm	Approx. 66.0 x 56.5 x 80.0mm
<b>Weight (without batteries)</b>	Approx. 350g	Approx. 300g	Approx. 127g
<b>Soft case</b>	SS-800	SS-600	SS-400



## Close-up Speedlight Commander Kit R1C1 (SU-800, two SB-R200s and all the accessories)

### Close-up Speedlight Remote Kit R1 (Two SB-R200s and all the accessories)



#### SB-R200 Wireless Remote Speedlight

Also available as a separate unit

[for D2 series, D200, D80, D40 series]

Two SB-R200 units are included with both the R1C1 and the R1. Each unit features a guide number of 10 (ISO 100, m) or 14 (ISO 200, m). When attached to a lens via the SX-1, the flash head can be tilted up to 60 degrees toward the optical axis of the lens or up to 45 degrees away from the lens.

#### Attachment Ring SX-1

Can hold SB-R200 Speedlights.

#### Extreme Close-up Positioning Adapter SW-11

For centering the light from the SB-R200 flash to an optical axis, which is especially effective in close-up shooting. Recommended for shooting distances within 15cm (lens to subject).



#### Diffuser SW-12

This milky-white panel diffuses light from a flash and softens shadows.

#### Flexible Arm Clip SW-C1

Allows attachment of items such as a diffuser. Can be attached to the guide groove of the Attachment Ring SX-1.



#### SU-800 Wireless Speedlight Commander

Also available as a separate unit


[for D2 series, D200, D80, D40 series]

Included only with the R1C1, the SU-800 features a commander function that can trigger the SB-R200, SB-600 and SB-800 wireless remote flash units. AF-Assist Illuminator, Target Light button and Test button are provided.



#### Speedlight Stand AS-20

For the stable placement of the SB-R200. A tripod socket is also provided.




#### Adapter Rings

Enable placing of Attachment Ring SX-1 on the front of the lens. Five filter attachment sizes (52mm, 62mm, 67mm, 72mm, 77mm) are available.



#### IR Panel for Built-in Flash SG-3IR

Attached to the camera's accessory shoe when the built-in Speedlight of a camera is used as a commander.



#### Color Filter Holder SZ-1

Enables filters to be attached to the SB-R200.



#### Color Filter Set SJ-R200

Change the mood of your close-up photography with four filters: Blue, Red, FL-G1 for fluorescent light and TN-A1 for incandescent light.



#### Case

- Soft Case for SU-800
- Soft Case for SB-R200
- Soft Case for SX-1
- Close-up Speedlight Kit Case

### Advanced Wireless Lighting System Compatibility

Cameras	Function	SB-800	SB-600	SU-800	SB-R200	Built-in Speedlight	Close-up Speedlight Kit
D2 series	Master unit	●				—	R1C1
	Remote unit	●	●		●	—	R1+SB-800
	Commander	●		●		—	
D200 D80	Master unit	●				●	R1C1
	Remote unit	●	●		●		R1
	Commander	●		●		●	

### Wireless Speedlight Commander SU-800 Specifications

#### Transmission mode

Infrared-pulse emitting communication using a flash discharge tube

#### Transmission range

Approx. 20m for the SB-800/SB-600, and approx. 4m for the SB-R200 at normal setting

#### Number of channels

4

#### Number of groups

3

#### Number of transmissions

Approx. 1,200

#### Transmission interval

Approx. 1 second

#### Flash light wavelengths

Approx. 800 to 1,000nm (infrared ray)

#### Flash coverage

Approx. 60° (vertical), approx. 78° (horizontal)

#### Display

LCD, ready-light

#### AF-Assist Illuminator

Automatically turns on when performing auto focus in dim light or in the dark

#### Power source

One 3V CR123A lithium battery

#### Dimensions (W x H x D)

Approx. 68 x 96 x 58mm

#### Weight (without battery)

Approx. 160g

### Wireless Remote Speedlight SB-R200 Specifications

#### Electronic construction

Automatic Insulated Gate Bipolar Transistor (IGBT) and series circuitry (for wireless remote flash unit only)

#### Guide number

10 (ISO 100, m), 14 (ISO 200, m)

#### Angle of coverage

24mm

#### Flash mode

i-TTL; D-TTL; M (Manual): full ~ 1/64 output (close-up), full ~ 1/128 output (commander)

#### Recycling time

Approx. 6.0 seconds (Manual at full)

#### Number of flashes

Approx. 290 (Manual at full)

#### Flash head tilt angle

Down to 60°, or up to 45°

#### Mounting foot

Dedicated shoe for Attachment Ring SX-1 or Speedlight Stand AS-20

#### Target light

White LED

#### Display

Ready-light

#### Power source

One 3V CR123A lithium battery

#### Dimensions (W x H x D)

Approx. 80 x 75 x 55mm

#### Weight (without battery)

Approx. 120g

# Flash Accessories

Expand the possibilities of your flash photography



For press photography as well as photographers more comfortable with wired flash synchronization, Nikon offers additional flash accessories. They are also indispensable for Nikon D-SLRs that lack a built-in wireless commander (such as D2 series, D40 series) for off-camera flash operation.



**Sync Terminal Adapter  
AS-15**

for D80, D40 series

The AS-15 is compatible with the D80 and D40 series which feature standard ISO-type accessory shoe but lack a sync terminal for large studio strobes.



SC-28



SC-29

**TTL Remote Cord  
SC-28/SC-29 (1.5m)**

for D2 series, D200, D80, D40 series

The TTL Remote Cord SC-28/SC-29 makes off-camera TTL flash control easy and assured. With the Nikon digital SLRs, the SC-29 also works as an external AF-assist illuminator.



**Power Bracket Unit  
SK-6A\* (for SB-800)**

[for D2 series, D200, D80, D40 series]

Not only does the SK-6A enable you to use the camera-mountable SB-800 as a grip-type flash, it also offers you remote-flash capability. Used as an external power source or in combination with the Speedlight's own power source, the SK-6A reduces minimum recycling time by nearly half while doubling the total number of flashes available.

\* The SK-6 may be substituted for the SK-6A in some countries.



**High-Performance Battery  
Pack SD-8A (for SB-800)**


[for D2 series, D200, D80, D40 series]

The SD-8A is designed for use with the SB-800 to shorten flash recycling time and enhance flash capacity. It accepts six 1.5V LR6 (AA-size alkaline), 1.2V KR-AA (R6/AA-size NiCd), 1.5V FR6 (AA-size lithium) or 1.2V R6/AA-size Ni-MH batteries.





*Capture NX software: master post-production*



© Joe McNally



## **Finally, software that brings out the best in everyone**

Post-production will never be the same. Simple and sophisticated by design, the new Capture NX is easy, intuitive and incredibly fast, turning complicated photo editing into a few clicks of the mouse. No more number crunching. No more guesswork. Thanks to Nikon's exclusive new U Point Technology, Capture NX does all the calculations for you, making it the first truly usable editing software for all levels of photographers. Image editing has never been so comprehensive, fast and fun!

## **Revolutionary: U Point Technology benefits**

### **Color Control Points:**

Easy to view and reposition, this amazing new system lets you adjust the color of any part of your image in a fraction of the time that other image editing tools require. A quick adjustment to a point's slider can adjust hue, saturation, brightness and more with immediate, sophisticated results.

### **Black, White, Neutral Control Points:**

These Control Points help correct color casts and refine color balance, adding more depth and dynamism to your images.

### **Show Selection for Accurate Control:**

This feature turns your image into black & white, with Control Point adjustments in white so that you know immediately what is affected.

### **Red-Eye Reduction:**

Now red-eye is a breeze to remove. Just place a Red-Eye Reduction Control Point over the eyes, click, and it's gone.

### **Easy-to-use Selective Tools**

Take advantage of commonly used enhancement tools. In addition to familiar selections like Lasso and Marquee, the Brush tool can now paint in or paint out an enhancement.


### **NEF (Nikon Electronic Format)**

With Capture NX, you'll never have to worry about damaging your original NEF file data, even after dozens of adjustments. All your original data and a thumbnail are saved automatically, along with a set of every enhancement command applied to it. Ordinarily, any change made to a file affects the original data, but Nikon's original technology makes this simple to avoid by converting original JPEG and TIFF images conveniently into NEF files. How's that for easy?




Kenji Miura – commercial photographer (Japan)

Both professionals and amateurs alike now have a new world of post-production opportunities available to them. The beauty of Capture NX is its simplicity. Conventional software requires a countless series of steps, with each individual effect a new stage in the process. For many photographers, this demanded frustrating amounts of memory and patience. Capture NX makes the process easy and intuitive. Whether it's the sky or skin tone, simply point to an area you want to adjust, click, and it's done! Hours of work can




now be accomplished in minutes, easily, and without requiring years of knowledge and experience.

#### **Color Control Points**





This unique interface makes editing incredibly simple. Just drag the sliders to the left or right. No other software is this intuitive.

#### **Show Selection**



#### **Red-Eye Reduction**



# Your file, your vision

## Capture NX software: master post-production

### ■ Enhancing the color of the sky using Color Control Points

1.



Place a Color Control Point on the sky.

2.



Sliders for Saturation, Hue and Brightness will appear. Adjust these as you wish.

3.



To repeat the effect in another area, duplicate the Control Point and place it somewhere else.

### ■ Correcting skin tones using the Color Picker

1.



Place a Color Control Point on any area of the subject's skin.

2.



Select the appropriate color from the skin tones provided in the center triangle of the Color Picker.

3.



Rotate the outside ring to adjust the hue to warmer or cooler.

### ■ Perfecting portions of an image using Brush Tool

1.




Choose the Brush Tool in the Selective Tools menu.

2.



Paint in the area you want to enhance. Painting out the enhancement is just as easy.


3.



Add any desired effects. Over 25 enhancements are available.


### ■ Seamless workflow from browsing to editing

1.




Choose browsing function to see images at a glance.

2.



Organize images by labeling and sorting.

3.



Start enhancing an image quickly and simply by double-clicking on it.



## Capture NX: Versatile Functions

### Browser (NEW)

Completely redesigned to sort, organize, compare, tag and improve images with more speed and agility.

### Batching

This simple, timesaving process automatically applies one or more enhancements to a series of images.

### Edit List (NEW)

For easier, more intuitive photo editing, the Capture NX Edit List helps you to track, cancel or add new modifications.

### Markers

Now it's possible to create multiple versions of your original NEF image, all within the original image file, saving you time as well as memory on your computer. Want to have a dozen versions of one image in a single file? No problem! You'll never have to search your computer to find other versions — they're all there with the original, and just a click away.

### Lens Correction Tools (some functions available for RAW files only) (NEW)

Vignette Control automatically reduces the effect of marginal illumination, Color Aberration Control reduces color-fringing effects, and Distortion Control reduces pincushion and barrel distortion effects.

### Color Management (NEW)

Lets you create a color profile so that colors are consistent from your first to last edit. Use the Soft Proof tool to see how a specific printer will recreate specific colors on your monitor. There's also the Capture NX print function, which lets you use an assigned profile to print your images.

## More useful software

### Camera Control Pro

#### Remote control for your Nikon D-SLR

When used in combination with an AF Nikkor lens (DX, D and G types), you can operate and control most of your Nikon D-SLR settings from a computer. Image files will be stored directly onto your hard disk, turning your computer into one large-capacity media card, which can be especially valuable during high-volume shooting such as studio work. Compatible with Wireless Transmitter WT-2/2A and WT-3/3A, Camera Control Pro also lets you control the camera via wireless LAN.

### Image Authentication Software (Windows only)

#### Protect the integrity of your valuable data (for D2Xs, D2X\*, D2Hs\*, D200\*)

When authenticity needs to be proven, Nikon's exclusive Image Authentication function indicates whether an actual image has been tampered with. It also lets you clarify any changes made item by item, such as the shooting date and any GPS information — indispensable for public works projects and the press.


\*1 Firmware upgrading is required to use this software.

### PictureProject

(provided free with all Nikon digital cameras)

Designed specifically for Nikon digital cameras, this specialized

### Color Aberration Control



Original image

Enhanced image

### Advanced Noise Reduction

**16-bit image compatibility (available for RAW and 16-bit TIFF files only)**

**D-Lighting** for pulling out more detail in both the highlights and the shadowy areas of your images.

**Most features, found in Nikon Capture 4, including some not shown here, are also included in Capture NX.**

### Capture NX System Requirements

Windows	
<b>CPU</b>	1.0GHz Pentium® III or higher (2.0GHz Pentium® 4 or higher recommended)
<b>OS</b>	Windows Vista™ (32 bit), Windows® XP Home Edition, Windows® XP Professional, Windows® 2000 Professional
<b>RAM</b>	256MB minimum (1.0GB or more recommended)
<b>Hard Disk</b>	200MB required for installation
<b>Display</b>	800 x 600 pixels (1024 x 768 or higher recommended) with 16-bit color (High Color/ thousands of colors) or 24-bit color (True Color/millions of colors) recommended
<b>Others</b>	<ul style="list-style-type: none"> <li>• CD-ROM drive required for installation</li> <li>• Internet connection required for some options</li> </ul>
Macintosh	
<b>CPU</b>	G4 or G5
<b>OS</b>	Mac® OS X (version 10.4 or later), Intel Core Duo, Intel Core 2 Duo, Intel Xeon
<b>RAM</b>	256MB minimum (1.0GB or more recommended)
<b>Hard Disk</b>	200MB required for installation
<b>Display</b>	800 x 600 pixels (1024 x 768 or higher recommended) with 16-bit color (High Color/ thousands of colors) or 24-bit color (True Color/millions of colors) recommended
<b>Others</b>	<ul style="list-style-type: none"> <li>• CD-ROM drive required for installation</li> <li>• Internet connection required for some options</li> </ul>

program helps you organize, edit, enhance, print and share your digital images. Picture Project also helps you e-mail images, as well as burn them to a CD or DVD.

### Do more with PictureProject using the following software:

#### • **nik Color Efex™ Pro 2.0 Express Edition**\*2

Offering fifteen kinds of digital filters for professional-level filtering effects, nik Color Efex™ Pro 2.0 Express Edition can help you apply considerably more artistry to your work.

#### • **PictureProject DVD Show**\*2

Turn your images and movies from your still digital camera into moving video clips set to music. You can even add sound effects and then burn them to a CD or DVD (Windows only).

#### • **PictureProject COOLPIX Remote Control**\*2

Control your COOLPIX S4, COOLPIX L1 and COOLPIX 8800/8400 cameras via computer. Simply connect the camera to your computer via USB cable.

\*2 Operation is not guaranteed with Windows Vista.





# Power when you need it

## Battery packs and power management



**Multi-Power  
Battery Pack MB-D200**

for D200

Runs on either six LR6/AA-size alkaline, FR6/AA-size lithium, or 1.2V R6/AA-size Ni-MH batteries, or one or two EN-EL3e rechargeable Li-ion batteries. Features two command dials, shutter release button and AF start button for vertical shooting.



**Multi-Power  
Battery Pack MB-D80**

for D80


Provides extra command dials, shutter release button and AE-L/AF-L button for vertical shooting. Runs on one or two EN-EL3e rechargeable Li-ion batteries, or six AA-size batteries.



**Rechargeable Li-ion  
Battery EN-EL4a**

for D2 series

These rechargeable batteries provide extended life and consistent power, even in cold conditions. Used together with your Nikon D-SLR, the camera's fuel gauge accurately displays the remaining charge, number of shots since last charge, and current battery life status. The EN-EL4a even gives notice when calibration is necessary.



**Rechargeable Li-ion  
Battery EN-EL3e**

for D200, D80



**Rechargeable Li-ion  
Battery EN-EL9**

for D40 series



**Quick Charger  
MH-21**

for D2 series

Enables charging of rechargeable Li-ion Battery EN-EL4a.



**Quick Charger  
MH-18a**

for D200, D80

Enables charging of rechargeable Li-ion Battery EN-EL3e.



**Quick Charger  
MH-23**

for D40 series

Enables charging of rechargeable Li-ion Battery EN-EL9.



# Communication technology for any location


## GPS cable/Wireless transmitters



**GPS Cable  
MC-35**

for D2 series, D200

Enables the Nikon D2-series/D200 digital SLRs to be connected to NMEA-0183 protocol-compatible GPS (Global Positioning System) units such as GARMIN™ and MAGELLAN™ for recording GPS positioning information and time signals synchronous to UTC (Universal Coordinated Time) within image data files during shooting.



**Wireless Transmitter  
WT-2/2A**

for D2 series


Wireless Transmitters WT-2/2A and WT-3/3A enable image data transfer via wireless LAN (Wi-Fi)\*. Simply mount one on the bottom of your camera and connect via USB cable, then any captured data can be transferred at high speed. And since they support various network and security protocols, these transmitters are compatible with a wide range of system environments. Camera Control Pro also enables wireless remote control from a personal computer via PTP/IP. With WT-3/3A, data transfer through a wired LAN via Ethernet network is also possible.

\* Conforming to the IEEE802.11b/g standard



**Wireless Transmitter  
WT-3/3A**

for D200



**Extended Range Antenna  
WA-E1**


for D2 series, D200

Increases the effective transmission range of wireless LAN from the normal 30m to approx. 150m.

Note: The WT-2/3 is sold in countries where governments approve the use of 13 frequency channels. The WT-2A/3A is sold in countries that authorize only the use of 11 frequency channels.



## Filters



**Neutral Color  
NC Filters**

Available in attachment sizes 39mm, 46mm, 52mm, 58mm, 67mm, these filters serve as lens protectors and do not affect color balance. In addition, multilayer coating prevents light reflection inside the glass, thereby improving color rendition.





# Steady shots — night or day


## Remote control accessories



**Remote Cord  
MC-36 (0.85m)**

for D2 series, D200


Enables remote firing of a camera, and setting of Interval Timer and Long Time Exposure. Incorporates illuminated LCD panel.



**Remote Cord  
MC-30 (0.8m)**

for D2 series, D200


Enables remote firing of a camera with trigger-lock function by keeping the shutter release button depressed — useful for bulb shooting.



**Remote Cord  
MC-22 (1m)**

for D2 series, D200

Useful for making connections to a shutter-triggering device, such as those activated by an infrared sensor to take pictures of wildlife after dark.



**Extension Cord  
MC-21 (3m)**

for D2 series, D200

For use with MC-30 or MC-22.



**Connecting Cord  
MC-23 (0.4m)**

for D2 series, D200

Connects two cameras for simultaneous or synchronized shutter release.



**Module Remote Control  
Set ML-3**

for D2 series, D200

The ML-3 offers remote control of two separate channels via an infrared LED beam to enable automatic camera operation from a distance up to about 8m. Features include auto-triggering and delayed shutter release, as well as single and continuous shooting.



**Adapter Cord  
MC-25 (0.2m)**

for D2 series, D200

Enables use of two-pin remote accessories: Remote Cord MC-4A, Remote Cord MC-12B, and Terminal Release MR-3.



**Remote Cord  
MC-DC1 (1m)**

for D80


Enables remote firing of the D80.



**Wireless Remote Control  
ML-L3**

for D80, D40 series

Enables wireless remote shutter release.



**Circular Polarizing  
Filters**

By reducing the light reflected from non-metallic surfaces, polarizing filters allow direct shooting through glass windows and minimize glare from water surfaces, sunlit trees and grass. Compatible with both color and monochrome photography.



**Gelatin Filter Holders  
AF-3, AF-4**

These holders accommodate gelatin or glass filters to a thickness of approx. 2mm. The AF-3 is used with 3-inch square gelatin filters and Nikkor lenses having an attachment size of 52/62/67/72/77mm. The AF-4 is used with 4-inch square gelatin filters and Nikkor lenses having an attachment size of 52/62/67/72/77/82/95mm.

Nikon also offers two dedicated hood options — the HN-36 for the AF-3 and the HN-37 for the AF-4. Several hoods of the same diameter can be stacked, depending on the focal length of the lens in use.



**Slip-in Circular Polarizing Filters**

Designed for use with telephoto lenses that provide a slip-in filter holder, these filters reduce glare from non-metallic surfaces such as glass and water. Simply turn the rotating ring on the holder to find the most effective position. These filters do not affect autofocus or auto exposure operation. Both the C-PL1L and C-PL3L feature 52mm diameter.

### Slip-in Circular Polarizing Filters—Compatible lenses

	C-PL1L	C-PL3L
AF-S VR 200mm f/2.8G IF-ED	—	✓
AF-S VR 300mm f/2.8G IF-ED	✓	—
AF-S 300mm f/2.8D IF-ED II	✓	—
AF-S 400mm f/2.8D IF-ED II	✓	—
AF-S 500mm f/4D IF-ED II	✓	—
AF-S 600mm f/4D IF-ED II	✓	—
AF-S VR 200-400mm f/4G IF-ED	✓	—

✓: Compatible —: Incompatible



# View with clarity and comfort

## Viewing attachments



### Right-Angle Viewing Attachment DR-5/DR-6

for D2 series, D200, D80, D40 series

Provides an upright, unreversed image for right-angle viewing. Individual eyesight adjustments are possible. The DR-5/DR-6 allows you to set the reproduction ratio to either 1:1 or 1:2.


The DR-5 is for cameras with a circular eyepiece (D2 Series); the DR-6 is for cameras with a rectangular eyepiece (D200, D80, D40 series). An eyepiece adapter is required when attaching the DR-5 to D2 series cameras.



### Eyepiece Magnifier DG-2

for D2 series, D200, D80, D40 series

The DG-2 provides 2x magnification of the central area of the finder image. Eyesight adjustment provided. Useful for critical focusing in close-up photography. Requires an eyepiece adapter.



### Eyepiece Adapter DK-22 DK-18

for D200, D80, D40 series

for D2 series

Enables attachment of Eyepiece Magnifier DG-2 to the camera's eyepiece. DK-22 is for cameras with a rectangular eyepiece. DK-18 is for cameras with a circular eyepiece.



### Magnifying Eyepiece DK-17M

for D2 series


Attached to a D2 series camera, the DK-17M magnifies the finder image approximately 1.2 times. Diopter adjustment range is widened at both the (+) and (-) sides.



### Magnifying Eyepiece DK-21M

for D200, D80

The DK-21M magnifies the D200 finder image by approximately 1.1 times.



### Eyepiece Correction Lenses DK-20C

for D200, D80, D40 series

An easy-to-use viewing and focusing aid which enables near- and farsighted photographers to view the finder image accurately without having to wear eyeglasses.



### Eyepiece Correction Lenses DK-17C

for D2 series

Five correction lenses from  $-3$  to  $+2\text{m}^{-1}$  for circular-eyepiece cameras.



### Antifog Finder Eyepiece DK-17A

for D2 series


A transparent plastic plate with a special surface coating that reduces fogging.



### Rubber Eyecup DK-19

for D2 series


Improves viewing comfort and prevents stray light from entering the viewfinder and washing out contrast.



Normal image

With DK-21M

## Interchangeable Focusing Screens



### Type B

for D2 series

Offers unobstructed viewing and easy focusing over the entire matte surface. Good for all general photography.

### Type E

for D2 series

Features grid patterns ideal for copying and architectural photography.

### Type V, W


D2X only

With the D2X, corner brackets indicate the rectangular area to be shot in High-speed Crop mode.

## Reproduction ratio

The reproduction ratio, which indicates the relationship between subject size and the size of the image on an image sensor, is determined by the distance to the subject and by the lens' focal length setting. If

Reproduction ratios using 50mm lens



1/8X

1/4X

Auto Extension Ring: 1/6.5x ~ 1.1x



# Close in on every subject


## Close-up accessories

(For information on the PB-6 and its limitations, see chart below)



**Bellows Focusing Attachment PB-6**

Renders reproduction ratios from about 1:1 to nearly 11x life-size, depending on the lens in use and whether the lens is mounted in normal or reverse position. Focal range of compatible lenses is from 20mm to 200mm. The lens extension covers the range from 48mm to 208mm, for producing frame-filling images of even the tiniest subjects.



**Extension Bellows PB-6E**

Attaches to the PB-6 for an astounding magnification of 23x life-size when using a 20mm wideangle lens in reverse position. With this combination, the continuously variable extension range is from 83mm to 438mm.




**Bellows Spacer PB-6D**

Enables a D2 series camera to move on the PB-6 rail without interference and allows horizontal/vertical changeover anywhere along the rail. Two PB-6Ds are needed when using the PB-6; three are needed when using the PB-6E.




**Slide Copying Adapter PS-6**

Used with the PB-6 and a Nikkor lens to make duplicate slides. Cropping of the original slide is possible.



**Macro Copy Stand PB-6M**

Attaches to the end of the PB-6 to convert it into a miniature copy stand or specimen stage.




**Macro Adapter Ring BR-2A**

Enables reverse-mounting of lenses. The BR-2A also increases the working distance for normal or wideangle lenses. Compatible with lenses having a 52mm-sized front attachment.




**Adapter Ring BR-3**

A handy adapter that converts the bayonet mount of reverse-mounted lenses to the 52mm thread used for filters and hoods.



**Focusing Stage PG-2**

Simplifies close-up focusing when using a tripod-mounted camera.  
(For D200, D80, D40 series)



**Auto Extension Rings \***

PK-11A\*\*, PK-12 and PK-13 auto extension rings fit between the camera body and lens singly or in combinations. When attached to an AI Nikkor lens, the lens retains automatic diaphragm and meter coupling functions. This gives you freedom to compose, focus and meter at the brightest, fullest aperture position without having to stop down the lens manually before shooting. (Exposure meter does not work with D80, D40 series.)

\* G-type lenses cannot be used.

\*\* Cannot be used with AF-S lenses.

### PB-6 Compatibility Chart

Depending on the camera used, certain accessories may be required when using the PB-6. Auto Extension Rings can increase lens extension.

D2 series	PK-12 or PK-13; two PB-6Ds (depending on camera position)
D200	PK-12 or PK-13
D200 with MB-D200	PK-13 and two PB-6Ds

the reproduced image is the same size as the subject, the reproduction ratio is one-to-one (1:1 or 1x). If the image is two times larger, the ratio is 2:1 or 2x. Nikon equipment for close-up photography offers a wide range of reproduction ratio capabilities.



1/2X



1X



2X



4X



8X

PB-6 (normal mounting): 1/1.1x ~ 4.0x

PB-6 (reverse mounting): 1.4x ~ 3.9x

PB-6 + PB-6E (reverse mounting): 1.4x ~ 8.4x



# SYSTEM DIAGRAM

## Prepare for the Possibilities


D2xs




D2Hs




### SPEEDLIGHTS (pp4-12)



### VIEWING ATTACHMENTS



### POWER SOURCES (p16)




### FOCUSING SCREENS (p18)




D200



### SPEEDLIGHTS (pp4-12)



### VIEWING ATTACHMENTS



### POWER SOURCES (p16)



### WIRELESS TRANSMISSION



D80




D40x




D40



### SPEEDLIGHTS (pp4-12)




### VIEWING ATTACHMENTS




### REMOTE ACCESSORIES




### CHMENT (p18)




### TEN-PIN REMOTE ACCESSORIES (p17)



### CLOSE-UP ACCESSORIES (p19)




### WIRELESS TRANSMITTER (p16)




### SOFTWARE (pp13-15)



### CHMENT (p18)



### TEN-PIN REMOTE ACCESSORIES (p17)



### STRAPS



### NSMITTER (p16)



### SOFTWARE (pp13-15)




### CAMERA CASE




### LENS AND BODY CAPS



### ACHMENT (p18)




### POWER SOURCES (p16)



### LCD MONITOR COVER



### ESSORIES (p17)



### SOFTWARE (pp13-15)



### CAMERA CASES



Note: Some multi-accessory combinations may not be compatible with certain cameras.

# NIKKOR LENS LINEUP

## *DX Nikkor Lenses*



AF DX Fisheye-Nikkor  
10.5mm f/2.8G ED

AF-S DX Zoom-Nikkor  
12-24mm f/4G IF-ED  
(2.0x)

AF-S DX Zoom-Nikkor  
17-55mm f/2.8G IF-ED  
(3.2x)



AF-S DX Zoom-Nikkor  
18-55mm f/3.5-5.6G ED II  
(3.0x)

AF-S DX Zoom-Nikkor  
18-70mm f/3.5-4.5G IF-ED  
(3.8x)

AF-S DX Zoom-Nikkor  
18-135mm f/3.5-5.6G IF-ED  
(7.5x)



AF-S DX VR Zoom-Nikkor  
18-200mm f/3.5-5.6G IF-ED  
(11.1x)

AF-S DX Zoom-Nikkor  
55-200mm f/4-5.6G ED  
(3.6x)

AF-S DX VR Zoom-Nikkor  
55-200mm f/4-5.6G ED  
(3.6x)

## *AF Zoom-Nikkor Lenses*



AF-S Zoom-Nikkor  
17-35mm f/2.8D IF-ED  
(2.1x)

AF Zoom-Nikkor  
18-35mm f/3.5-4.5D IF-ED  
(1.9x)

AF Zoom-Nikkor  
24-85mm f/2.8-4D IF  
(3.5x)

AF-S VR Zoom-Nikkor  
24-120mm f/3.5-5.6G IF-ED  
(5.0x)

AF-S Zoom-Nikkor  
28-70mm f/2.8D IF-ED  
(2.5x)



AF-S VR Zoom-Nikkor  
70-200mm f/2.8G IF-ED  
(2.9x)

AF Zoom-Nikkor  
70-300mm f/4-5.6D ED  
(4.3x)

AF-S VR Zoom-Nikkor  
70-300mm f/4.5-5.6G IF-ED  
(4.3x)



AF Zoom-Nikkor  
80-200mm f/2.8D ED  
(2.5x)

AF VR Zoom-Nikkor  
80-400mm f/4.5-5.6D ED  
(5.0x)

AF-S VR Zoom-Nikkor  
200-400mm f/4G IF-ED  
(2.0x)

## *AF Single-Focal-Length Nikkor Lenses*



AF Nikkor  
14mm f/2.8D ED

AF Fisheye-Nikkor  
16mm f/2.8D

AF Nikkor  
20mm f/2.8D

AF Nikkor  
24mm f/2.8D

AF Nikkor  
28mm f/2.8D

AF Nikkor  
35mm f/2D

AF Nikkor  
50mm f/1.4D

AF Nikkor  
50mm f/1.8D

AF Micro-Nikkor  
60mm f/2.8D



AF Nikkor  
85mm f/1.4D IF

AF Nikkor  
85mm f/1.8D

AF DC-Nikkor  
105mm f/2D

AF-S VR Micro-Nikkor  
105mm f/2.8G IF-ED

AF DC-Nikkor  
135mm f/2D

AF Nikkor  
180mm f/2.8D IF-ED

AF-S VR Nikkor  
200mm f/2G IF-ED



AF Micro-Nikkor  
200mm f/4D IF-ED

AF-S VR Nikkor 300mm  
f/2.8G IF-ED

AF-S Nikkor  
300mm f/4D IF-ED

AF-S Nikkor  
400mm f/2.8D IF-ED II

AF-S Nikkor  
500mm f/4D IF-ED II

AF-S Nikkor  
600mm f/4D IF-ED II

AF-S Teleconverter  
TC-14E II

AF-S Teleconverter  
TC-17E II

AF-S Teleconverter  
TC-20E II



# NIKON DIGITAL SLRs

You want performance. You need consistency. You're searching for the best image quality in the business. You're looking in the right place. Professionals and passionate amateurs around the world understand that Nikon means quality and dependability. Which digital SLR is right for you?



## D2xs Professional digital SLR: Integrated like no other

- 12.4 effective megapixels for 4,288 x 2,848 pixel images
- Exclusive Nikon DX Format CMOS imaging sensor and high-speed 4-channel independent data output
- Continuous shooting at 5 fps (Full Image) or 8 fps (6.8 megapixel High-speed Crop Image)
- High-speed, high-precision 11-area AF system with 9 cross-type AF sensors
- LCD monitor with 170 degree of viewing angle
- i-TTL flash control supports the Creative Lighting System
- Quick startup and short 37-millisecond shutter release time lag

## Dependable high-speed professional digital SLR D2Hs

- 4.1 effective megapixels for 2,464 x 1,632 pixel images
- Exclusive Nikon DX Format JFET imaging sensor LBCAST
- Image-processing engine with refined ASIC
- Continuous shooting at approx. 8 fps for up to 50 consecutive JPEG or 40 RAW (NEF)
- High-speed, high-precision 11-area AF system with 9 cross-type AF sensors
- 3D Color Matrix Metering II featuring 1,005-pixel RGB sensor
- i-TTL flash control supports Creative Lighting System



## D200 Precision crafted, for the ultimate digital SLR experience

- 10.2 effective megapixels for 3,872 x 2,592 pixel images
- Exclusive Nikon DX Format CCD imaging sensor and high-speed 4-channel independent data output
- Continuous shooting at 5 fps up to 37 consecutive JPEG or 22 RAW (NEF)\*
- 3D Color Matrix Metering II featuring 1,005-pixel RGB sensor
- High-performance System LSI
- High-speed, high-precision 11-area AF system
- Built-in Speedlight supports Creative Lighting System

\* When using a SanDisk SDCFX3 (Extreme III), SDCFH (Ultra II) or Lexar Media 80X WA CompactFlash™ card

## High performance that satisfies all shooting styles D80


- 10.2 effective megapixels for 3,872 x 2,592 pixel images
- Exclusive Nikon DX Format CCD imaging sensor and high resolution image processing engine
- 3D Color Matrix Metering II featuring 420 segment RGB sensor
- Seven automated Digital Vari-Program modes
- Broad ISO-equivalent sensitivity range (100-1,600)
- High-performance i-TTL built-in flash and Creative Lighting System compatibility



## D40x/D40 Outstanding picture quality that's easy for everyone

- 10.2 (D40x)/6.1 (D40) effective megapixels; Nikon DX format CCD
- Advanced digital image processor
- 3D Color Matrix Metering II featuring 420-segment RGB sensor
- Intuitive and ergonomically designed control
- Eight automated Digital Vari-Programs, including Auto (Flash Off) mode
- Advanced AF system with refined algorithms
- "Assist Images" to help select appropriate settings for many camera features
- Built-in Flash with i-TTL flash control

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.  
Macintosh® is a registered trademark or a trademark of Apple Inc. in the United States and/or other countries.  
Specifications and designs are subject to change without any notice or obligation on the part of the manufacturer.  
©2006/7 NIKON CORPORATION


	<b>WARNING</b>	<b>TO ENSURE CORRECT USAGE, READ MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT</b>
--	----------------	--

### Other Nikon product brochures

Brochures are available for all Nikon digital imaging products. Please consult your nearest authorized dealer, or check your local Nikon website via <http://nikonimaging.com/global/about/worldwide.htm>



D2Xs



D2Hs



D200



D80




D40x



D40



Nikkor Lenses



COOLPIX Lineup



Capture NX

You can also download brochures at <http://nikonimaging.com/global/products/brochure/>



Visit the Nikon Europe website at: [www.europe-nikon.com](http://www.europe-nikon.com)



#### NIKON CORPORATION

Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku,  
Tokyo 100-8331, Japan  
<http://nikonimaging.com/>

Printed in Holland Code No. 8CE30600 (0707/B)K

Nikon Nordic AB Danish Branch Office Ørestads Boulevard 67-1, DK-2300 København S, Denmark [www.nikon.dk](http://www.nikon.dk)  
Nikon U.K. Ltd. NIKON House, 380 Richmond Road, Kingston, Surrey KT2 5PR, U.K. [www.nikon.co.uk](http://www.nikon.co.uk)  
Foto Distributors 516 Kyalami Boulevard, Kyalami Business Park, Midrand 1684, South Africa [www.nikonsa.co.za](http://www.nikonsa.co.za)  
NIKON CANADA INC. 1366 Aerowood Drive, Mississauga, Ontario, L4W 1C1, Canada [www.nikon.ca](http://www.nikon.ca)